

KOMATSU

C.S. NO.	KOMATSU O.E.M. REF.NO.	MODEL & DESCRIPTION	NO. CYL	CYL. DIA.	HEAD TYPE NO.	PISTON				PIN		REMARKS
						LONG	COMP. DIST.	RING		DIA	LONG	
								COMP.	OIL			
21103J	6207-31-2121	6D95	6	95.0	198	94.2	51.2-19.6-0.9	1-2.51dk 1-2.25k	1-4.0	30	74	
21110J	6207-31-2180	6D95	6	95.0	198	94.2	51.2-19.6	2-2.4dk	1-4.0	30	74	
21109J	6204-31-2121	6D95 NEW	6	95.0	100	94.4	51.3-18.8	2-2.0	1-4.0	30		
21103JU	6207-31-2141	S6D95	6	95.0	198	94.2	51.2-19.6-0.9	1-2.51dk 1-2.25k	1-4.0	30	74	BOWL: 56MM 2 valves
21103JUI	6207-31-2110	6D95	6	95.0	198	94.2	51.2-20.4-0.9	1-2.63dk 1-2.27k	1-4.0	30	74	
21103JUG		S6D95	6	95.0	198	94.2	51.2-19.6-0.9	1-2.5dk 1-2.0	1-4.0	30	74	
21119J	6735-31-2110 6735-31-2111	S6D102	6	102.0	274	105.4	71.6-22.1	1-3.0dk 1-2.4	1-4.0	40	83	
21126J		S6D102	6	102.0	314	97.8	57.8-18.9	1-3.15k 1-2.04k	1-4.0	34	84	
21114J	6131-32-2120	4D105	4	105.0	314	107.5	69.0-22.9	1-3.0 dk 1-2.5	1-5.0	38	88	
21116J	6136-32-2110	PC200-2	6	105.0	198	107.7	69.2-22.8-1.8	1-3.0 1-2.5	1-5.0	40	84	
21101J	6137-32-2130	SA6D105	6	105.0	198	107.7	69.2-23.7	1-3.23dk 1-2.58k	1-5.0	40	86	
21108J	6137-32-2010 6137-32-2110	SA6D-105	6	105.0	198	107.7	69.2-22.2	1-3.23dk 1-2.58k	1-5.0	40	86	
21115J	6136-31-2112	6D105	6	105.0	304	107.5	69.0-22.6	1-3.0 1-2.5	1-5.0	40	84	
21115JU	6137-31-2020	6D105	6	105.0	354	107.5	69.0-22.7	1-3.0dk 1-2.5k	1-5.0	40	86	
21104J	6222-31-2110	SA6D108	6	108.0	198	113.8	66.7-21.5-2.2-1.1	1-2.52dk 1-2.69dk	1-4.0	45	85	
21124J	6222-33-2110	S6D108 gallery cool	6	108.0	274	113.8	66.7-26.0	2-2.5K	1-4.0	45	85	
21133J		6D108	6	108.0	274	113.8	66.7-25.9	1-2.37dk 1-2.61dk	1-4.0	45	85	
21102JU	6138-32-2110	6D110	6	110.0	198	116.2	69.2-22.8-2.8-1.9	1-3.14dk 1-2.57k	1-5.0	40	91	BOWL: 62MM
21102JU1	6138-31-2010	6D110-1	6	110.0	354	116	69.0-20.5	1-3.0dk 1-2.5k	1-5.0	40	91	
21102JU2	6138-32-2110	S6D110	6	110.0	198	116.2	69.2-20.4-3.3-1.8	1-3.0dk 1-2.5k	1-5.0	40	91	
21102J	6138-32-2120	SA6D110	6	110.0	198	116.2	69.2-13,-22	1-3.14dk 1-2.57k	1-5.0	40	91	BOWL: 66MM
21131J	6110-33-2132	4D120	4	120.0	106	134.9	90-7.1-6-4.3-1.1	1-3.5 1-2.5	1-5.5	44	100	
21111J	6150-31-2112	6D125	6	125.0	333	131.1	80.1-25.7	2-2.5dk	1-4.0	48	104	
21112J	6151-31-2171 6151-31-2150	6D125	6	125.0	333	131.1	80.1-24.7	2-2.5dk	1-4.0	48	104	w/oil jet recess

