

# VOLKSWAGEN

C.S. NO.	O.E.M. REF.NO.	MODEL& DESCRIPTION	NO. CYL	CYL. DIA.	HEAD TYPE NO.	PISTON				PIN		REMARKS
						LONG	COMP. DIST.	RING		DIA	LONG	
								COMP.	OIL			
29119		GY1300	4	75	1	65.6	38.6	1-1.75 1-2.0	1-4.0	20.0	63.0	
29123		VW1300	4	75	261	71.8	39.8-2.9	1-1.5 1-1.75	1-3.0	20.0	57.0	
29111	056-107-065S		4	76.5	5	74.0	42.0-6.4	1-2.0 1-2.5	1-4.0	22.0	63.0	
29141		1.4L	4	76.5	261	70.6	37.9-2.2	1-1.2 1-1.5	1-2.5	20.0	56.8	
29116J			4	76.5	215	71.7	41.7-1.6	1-1.8 1-2.0	1-3.0	24.0	64.0	
29122			4	76.5	215	71.8	41.5-1.7	1-1.75 1-2.0	1-3.0	24.0	64.0	
29122J			4	76.5	215	71.8	41.5-1.7	1-1.75 1-2.0	1-3.0	24.0	64.0	
29117J			4	76.5	215	76.6	44.7-1.8	1-1.8 1-2.0	1-3.0	22.0	64.8	
29121	RP83021		4	79.5	5	73.8	41.8-6.1	1-1.75 1-2.0	1-4.0	22.0	63.0	
29112	049-107-065A		4	79.5	5	74.0	42.0-6.7	1-1.8 1-2.5	1-5.0	22.0	63.0	
29113	049-107-065K		4	79.5	5	77.3	45.3-5.3	1-1.7 1-2.0	1-4.0	22.0	63.0	
29134J	029 9600	1.9 ST	4	79.5	215	71.6	45.6-1.9	1-1.8 1-2.0	1-3.0	26.0	66.0	
F-29153L/RJY	038-107-065KE 038-107-065KF	1.9L DIESEL	4	79.5	100	68.8	45.8-17.3-0.7	1-1.75 1-2.0	1-3.0	26.0	66.0	
F-29153L/RJYI	038-107-065JL 038-107-065JM	1.9L DIESEL	4	79.5	112	68.8	45.8-17.3	1-1.75 1-2.0	1-3.0	26.0	66.0	
F-29155L/RJ	038-107-065-AA 038-107-065-AB	1.9 TDI	4	79.5	342	71.8	45.8-17.8-1.0	1-1.75 1-2.0	1-3.0	26.0	66.0	
29142		1.8L	4	81	261	53.8	32.7-3.0-0.7	1-1.5 1-1.7	1-3.0	20.0	57.0	
29120B	RP83030		4	81	225	62.3	33.4-1.2	1-1.5 1-1.75	1-3.0	20.0	56.5	
29120IP			4	81	225	62.3	33.4-5.5	1-1.5 1-1.75	1-3.0	20.0	56.5	
29118		SATANA	4	81	225	62.6	33.7-9.3	1-1.5 1-1.75	1-3.0	20.0	56.0	
29139			4	81	261	53.6	32.05+0.6-3.3	1-1.5 1-1.8	1-2.0	20.0	57.0	
29126			4	81	331	66.9	35.5+2.4	1-1.5 1-1.75	1-3.0	20.0	57.0	

C.S. NO.	O.E.M. REF.NO.	MODEL& DESCRIPTION	NO. CYL	CYL. DIA.	HEAD TYPE NO.	PISTON				PIN		REMARKS
						LONG	COMP. DIST.	RING		DIA	LONG	
								COMP.	OIL			
29138	071-107-065C	AAA GRAPHITED SKIRT	6	81	337	55.3	32.4+1.9-8.1	1-1.5 1-1.75	1-3.0	20.0	57.0	
F-29152		1.8 5VT	4	81	376	53.7	32.7-1.5	1-1.5 1-1.75	1-2.0	20.0	59.0	
29143		8V	4	82.5	120	63.5	31.4-0.5-5.5	1-1.2 1-1.5	1-2.0	21.0	59.0	
29140		B4 SKIRT MOS2	4	82.5	225	51.7	30.6+0.8	1-1.2 1-1.5	1-2.0	21.0	56.0	
29136	032-107-065J	SKIRT MOS2	4	82.5	261	51.7	31.7-1.2-7.3	1-1.2 1-1.5	1-2.0	21.0	56.0	
F-29150	06A-107-065AE	2.0AE SKIRT MOS2	4	82.5	261	51.0	30.0-6.6-0.7	1-1.2 1-1.5	1-2.0	19.0	42.0	
F-29151		2.0AA SKIRT MOS2	4	82.5	261	51.0	30.0-6.6-0.7	1-1.2 1-1.5	1-2.0	20.0	52.5	
29137			4	85.5	1	61.0	33.9	2-2.0	1-5.0	22.0	63.5	
29101HA			4	85.5	1	82.04	38.96	2-2.0	1-5.0	22.0	71.95	
29105	311-198-069B		4	85.5	1	82.5	39.5	2-2.0	1-5.0	22.0	72.0	
29101	P1F13298-D		4	85.5	005	82.4	39.4-3.0	2-2.0	1-5.0	22.0	72.0	
29106			4	87	1	82.5	39.5	2-2.0	1-5.0	22.0	72.0	
29106A	P1F13223-C	LJ1300	4	87	1	83.0	40.0	2-1.5	1-5.0	22.0	72.0	
29106B			4	88	1	82.5	39.5	2-2.0	1-5.0	22.0	72.0	
29114			4	90	10	80.0	42.0-1.5	2-2.0	1-5.0	24.0	78.0	
29135			4	90.5	1	60.6	35	1-1.5 1-2.0	1-4.0	22.0	63.0	
29115				90.5	1	72.0	39.7	2-2.0	1-5.0	22.0	75.0	
29135A			4	92	1	60.6	35	1-1.5 1-2.0	1-4.0	22.0	63.0	
29107	P1F13139-J		4	92	1	74.3	39.6	2-2.0	1-4.025	22.0	72.0	
29103			4	93	10	80.0	42.0-4.3	2-2.0	1-4.0	24.0	78.0	
29104	022-198-075A		4	93	12	82.1	42.1+2.0	2-2.0	1-4.0	24.0	78.0	
29129U			4	94	1	58	35.06	1-1.8 1-2.0	1-4.0	24.0	70.0	

